OREOS M20 The Electric minibus








Electric by PVI

100% electric Minibus 4,5T 19 passengers – Flat & low floor @ 250mm Autonomy up to 150 km– Fast charge @22kW



No CO2 emission / low noise emission Regenerative braking / Connected vehicle / Electric AC

OREOS M20 The Electric minibus



Dimensions & Configuration		Powertrain & H2 system & Weight & Performances	
Length	6 225 mm	Туре	Traction
Cabin width with/without mirrors	2 470 / 2 070 mm	Electric motor	Renault
Height	2 750 mm	Power / Torque	57 kW / 225 Nm
Front overhang	842 mm	Lithium-lon battery capacity	33 kWh
Wheelbase	4 332 mm	Battery voltage	400 V
Rear overhang	1 040 mm	Onboard charger	7 kW
Floor height Front/Rear	250/350 mm	(possible charge @22kW via an external cha	arging plug)
Internal height Front/Rear	1 900/1 800 mm		
Minimum ground clearance	160 mm	GVW	4 500 kg
Internal width	1 765 mm	Front axle capacity (min / max)	1 450 kg / 1 850 kg
Total turning radius	8 000 mm	Rear axle capacity (min / max)	1 550 kg / 2 800 kg
Turning radius between sidewalk	7 800 mm	Payload	1 500 kg
Suspensions Front/Rear Indepe	ndent mechanical suspensions		(h
Types Front/Rear 23	5/75 R16 (single wheels)	Charging time @7kW	6 hours @80%
Double electric sliding door with anti-pinch system		Charging time @ 22kW	2 hours @80%
9 seated passengers + 10 standing passengers + driver		Max speed	70 km/h
7 seated passengers + 9 standing passengers + 1 wheelchair + driver		Autonomy	up to 150 km without A/C
Basic equipment		Options	
ABS / Drivers airbag / ESP / LDWS / AEBS		Electric air conditioning system for passengers	
Suspended driver's seat		Window slider	
Hill start system		Reverse alarm & camera & radar	
Electric air conditioning & heating system for the driver		Anti-fog lights	
Additional thermal heating system for passengers		Destination signs (Front + lateral + rear + internal)	
Heated rear-view mirror		Electrical predispositions	
Onboard computer & Radio R&GO		Passengers counting system	
Fog maker system		Camera video control system	
Bus stopping sign		Internal TFT screen for passengers	
Roof mounted continuous lighting strips		Passenger ticketing system	
Manual flip ramp to side entrance		USB kit for passengers	
Specific wheelchair area		Cash area for the driver	
Non slip vinyl walkway floor covering TBC		Digital breathalyser	
Charging cable 32A - 6m		Specific covering or painting	







NOTA : Pictures and figures are given just for information